


Cable Solutions for Solar & Energy Storage Systems

HELUKABEL® SOLAR POWER






Solar Power

The demand for renewable energy is rapidly increasing worldwide and solar energy is one of the most important and cleanest energy sources for this, along with wind and water. In order to take advantage of them, photovoltaic systems are used - for homes, industrial halls, office buildings, farms and floating systems. The environmental conditions vary greatly; however, photovoltaic systems are almost always exposed to weather, humidity, UV radiation and strongly fluctuating temperatures.


Reliable and durable cabling of the individual solar modules with each other and the cabling to the inverters and storage systems is crucial for efficient operation of the systems. This is where cables are needed that reliably withstand all external influences - this is the only way to get the energy generated to where it is needed. As a leading manufacturer and supplier of electrical connection technology, HELUKABEL has decades of experience in the photovoltaic industry - and supplies the ideal cables and wires as well as the right accessories for every application.



We offer a broad range of products, from DC string cables for connecting solar panels, to earth and medium-voltage cables for connection and grid feed-in, to fibre optic and data cables for networks and communication. In addition, we offer integrated cable management systems including connectors, plugs, hoses, glands, housings and tools, as well as pre-assembled cables. Our experts are particularly competent in developing customised

solutions for special applications - and thanks to our global presence, all local and regional requirements such as environmental conditions and design standards can be met.

HELUKABEL thus supports manufacturers, installers and operators of photovoltaic systems worldwide in generating clean, sustainable and renewable energy.



Solutions for Photovoltaic Systems

For further information, please refer to the corresponding data sheets at: www.helukabel.com/ 999999 en (replace the red numbers with the corresponding part no.)



STRING CABLES (DC)

SOLARFLEX *-X H1Z2Z2-K

1500 V DC, EN 50618, copper wire, tinned, finely stranded acc. to DIN VDE 0295 CI. 5 / IEC 60228 CI. 5 resistant to: UV radiation, ozone, weathering effects, water. Halogen-free and flame retardant. Used for cabling solar modules. Suitable for direct burial. Recommendation: Installation in pipes. Available in various colours, cross sections and drum sizes Part no. 713529



Solar connectors

MC 4 1000V PV-male / female cable coupler Part no. 905206 / 905207

MC 4-Evo 2 1500 V PV-male / female cable coupler Part no. 11020678 / 11020682

PV MC4 male & female Branch connector

Inline Fuse Connectors

Extension solar cable 6 mm²
MC4 male to MC4 female 2, 8,10 m.
Part no. 11023765 / 11023767 / 11023767
Additional fabrication options available upon request.

Battery connection cable set
Battery cable 2XNSGAFÖU. With and without cable lugs.
Available in various cross sections.
Part no. 11023261

Moulded Assemblies











2 POWER CABLES (AC)

NYY-J / NYY-O

Power / control cable, 0.6/1 kV, VDE approved, bare copper conductor, PVC insulation, PVC sheath

Part no. 32001



N2XY-J / N2XY-O

Power distribution cable, 0.6/1 kV, VDE approved, higher current carrying capacity, bare copper conductor, XLPE insulation, PVC sheath

Part no. 32850



NAYY-J / NAYY-O

Power distribution cable, 0.6/1 kV, VDE approved, aluminum conductor, PVC insulation, PVC sheath

Part no. 32301



NA2XY-J / NA2XY-O

Power distribution cable, 0.6/1 kV, VDE approved, current carrying capacity, aluminum conductor, XLPE insulation, PVC sheath

Part no. 33113



N2XH-J / N2XH-O

Power / control cable, 0.6/1 kV, halogen-free, bare copper conductor, XLPE insulation, TPO sheath

Part no. 53558



(N)A2XH-J / (N)A2XH-O

Power / control cable, 0.6/1 kV, halogen-free, aluminum conductor, XLPE insulation, TPO sheath

Part no. 50073



HELUPOWER® 1000 RV-K

Connection cable, direct burial, 90°C, bare copper conductor, XLPE insulation, PVC sheath

Part no. 11003798



H07RN-F

Connection cable, oil-resistant, weather-resistant, bare copper conductor, rubber insulation and sheath

Part no. 37001



HELUPOWER® H07RN-F LS0H

Connection cable, oil-resistant, halogen-free, bare copper conductor, special rubber insulation and sheath

Part no. 30737



NSGAFÖU 1,8/3 kV

short-circuit and earth-fault proof p to 1kV, copper wire tinned, high mechanical stress, flame-retardant and oil-resistant





HELUPOWER® THERMFLEX® 145

Tinned stranded copper wire, temperature resistant, improved behavior in case of fire, XLPE insulation and sheathing

Part no. 17001667



NF-USE NF XPC 32-321 U-1000R2V

Rigid industrial power cable, bare copper conductor, low voltage, 0.6/1kV, XLPE insulation, PVC sheath

Part no. 19000700



NF-USE NF XPC 32-321 U-1000AR2V

rigid industrial power cable, aluminum conductor, low voltage, 0.6/1kV, XLPE insulation, PVC sheath

Part no. 19002046



WK POWERLINE® ALU

Standard 1 KV, 1.8/3KV suitable for underground installation, robust, flexible, PUR sheath, UV and oil resistant

Part no. 707647



Local versions and standards available on request.



MEDIUM VOLTAGE CABLES (GRID FEED-IN)

N2XSY

6/10 kV, 12/20 kV, 18/30 kV, VDE approved, bare copper conductor, XLPE insulation, PVC sheath

Part no. 32400



N2XS2Y

6/10 kV, 12/20 kV, 18/30 kV, VDE approved, bare copper conductor, XLPE insulation, PE sheath

Part no. 32480



N2XS(F)2Y

6/10~kV, 12/20~kV, 18/30~kV, VDE approved, bare copper conductor, XLPE insulation, PE sheath, longitudinally waterproof

Part no. 32560



N2XS(FL)2Y

6/10 kV, 12/20 kV, 18/30 kV, VDE approved, bare copper conductor, XLPE insulation, PE sheath, laterally waterproof

Part no. 33054



NA2XSY

6/10 kV, 12/20 kV, 18/30 kV, VDE approved, aluminum conductor, XLPE insulation, PVC sheath

Part no. 32440



NA2XS2Y

6/10 kV, 12/20 kV, 18/30 kV, VDE approved, aluminum conductor, XLPE insulation, PE sheath

Part no. 32520



HELUKABEL[®]

Local versions and standards available on request.



COMMUNICATION CABLES & CONNECTORS

PAAR-TRONIC-Li-2YCYv

Low capacitance, EMC-preferred type

Part no. 21129



Fibre optic cables (SM and MM)

HELUCOM® PACT A-DQ(ZN)B2Y

3000N, central, single mode E9/125μm

Part no. 11017392



2700N, stranded, single mode E9/125 μm

Part no. 80188

HELUCOM® A-DQ(ZN)(SR)2Y

1500N, steel armoured, central, single mode E9/125µm

Part no. 803928



Fibre optic equipment



Customised fibre optic harnesses



Loose tube cable with splitting body and retraction protection



Robust, moulded splitting body



Mini-conductor cable



4 COMMUNICATION CABLES & CONNECTORS

Ethernet copper data cables

HELUKAT® 600A S/FTP PVC/PVC

LAN cable, Cat.7e, outdoor

Part no. 801147

HELUKAT® 600E S/FTP PVC

LAN cable, Cat.7e, direct burial

Part no. 802167

HELUKAT® 600AE S/FTP FRNC/ PE

LAN cable, Cat.7e, direct burial, armoured

Part no. 802168

HELUKAT® 600 S/FTP FRNC

LAN cable, Cat.7e, tight cable channels / duplex version

Part no. 80810 / 81446









Ethernet patchcords

Industrial Ethernet Patchcords (IP protected)

RJ45-IP20 180°, Cat.6A, normal flexible application

Part no. 806618



Ethernet Patchcords RJ45

S/FTP halogen-free, Cat.6, class E

Part no. 806253



HELUKAT500IND ExtraFlex RJ45

S/FTP Cat.6_A, RJ45-IP20 180°

Part no. 11007749



BUS system cables

E-BUS / KNX

PVC + FRNC, fixed installation

Part no. 81663 / 804042



E-BUS / KNX

PE, fixed installation, direct burial

Part no. 802800

HELUKABEL® KNX-BUS PE

CAN Bus

PVC, fixed installation, indoor





RJ45 copper connector



Part no. 11022946



Part no. 804544



Part no. 11017885



Part no. 11017766



Part no. 11017767

Part no.	Cat.	Connector	Pins	Core Ø in mm	Cable Ø in mm	AWG solid	AWG stranded	UL	Class	Standard
11022946	6 _A	straight	8	max. 1.6	5.5-10.0	22-24	22/7 – 27/7	yes	IP20	TIA 568 B
804544	6 _A	straight	8	max. 1.6	5.0-9.5	22-26	22-27/7		IP20	TIA 568 A
11017885	6 _A	straight	8	1.0-1.4	6.0-7.5	26-23	26-23		IP20	TIA 568 A/B
11017766	6 _A	straight	8	1.0-1.4	7.0-8.5	26-23	26-23		IP20	TIA 568 A/B
11017767	8	straight	8	1.4-1.65	7.0-8.5	24-22	24-22		IP20	TIA 568 A/B

ACCESSORIES

Glands



HELUTOP HT-MS-EP4

Brass, nickel plated, EMC-cable gland with integrated contact system for safe, quick assembly and contacting

Part no. 905181



HSK-PVDF

Polyvinylidene fluoride for use at high temperatures, under long-term UV exposure

Part no. 97571



HELUTOP HT

Plastic, polyamide PA6 cable gland with vibration protection Part no. 93908



HELUTOP Easy

Threadless, for quick installation with patented spring/snap system without tools

Part no. 908054

Cable fastening systems





Cable clamps K / KS

For fastening single and multi-conductor cables (K) or in a triangular connection (KS). Available on request



Heluclamp D1-M

For the short-circuit-proof fastening of single-core or multi-core medium and high voltage cables



ACCESSORIES

HELUCOND corrugated tubes



PΡ

Polypropylene, for medium stress applications **Part no. 920170**

PA6-UL

Polyamide 6, for heavy duty applications

Part no. 920384

PA12

Polyamide 12, highly flexible, high load rating for heavy-duty applications

Part no. 920156



CO-PA

Polyamide 6, UV-resistant, halogen-free, dividable

Part no. 90061

CO-PP

Polypropylene, halogen-free, dividable

Part no. 97496

CO-PP-UV

Polypropylene, UV-resistant, halogen-free, dividable **Available upon request**

Medium voltage straight joint



MSVM-S Medium voltage straight joint Heat-shrinkable - Single core.

For connecting cables with differing cross-sections, conductor materials and cable designs with all single-core plastic power cables with external conductor layer up to 18/30(36)kV

Part no. 93107





MSVM-S Medium voltage straight joint Heat-shrinkable - Triple core.

For connecting cables with differing cross-sections, conductor materials and cable designs with all 3-core plastic power cables with external conductor layer up to 18/30(36)kV

Part no. 93135

Drum unwinder / decoiler



HELUTOOL 250 pocket / 190 Drum unwinder

For simple reeling of cable drums

Part no. 903716 / 93529



TROMBOI 500 Drum decoiler

Shaftless, for drums with different diameters and weights



Others



KMK-PA-MB / KM-EMV(EMC)
Counternuts
Part no. 97816



TY-MX
UV-resistant cable tie
Part no. 91052



EKIEnd caps with internal adhesive **Part no. 97642**

Cable lugs



HELU-S-PK-AL-FG-VZN Aluminum, tinned, FG, extruded, straight ring design Part no. 909853



HELU-S-PV-AL/CU
Press connector for aluminum
conductors, strain relieved
Part no. 907836



HELU-S-PK-AL/CUAluminum/Copper, non-insulated, straight compression lug **Part no. 907568**

Tools



WK-APW 18 Hydraulic hand press For processing cable lugs and connectors up to 1000 m² Part no. 909871



HELUTOOL D20 cable shear Cuts Cu and Al cables smoothly and clean without crushing, solid / stranded Part no. 904933



Equipped with: Stripping pliers 4-10 mm² Crimping pliers PEW12, cable shear Part no. 11009092

Contact

1052 Schooner Ave, Laser Park. Honeydew +27(0) 11 462 8752 sales@helukabel.co.za www.helukabel.co.za

KWAZULU NATAL 31 Hillclimb Road,

Gauteng

31 Hillclimb Road, Westmead. Pinetown Kwazulu Natal +27(0) 81 577 7375 kznsales@helukabel.co.za www.helukabel.co.za

CAPE TOWN

15 Longclaw Drive, Montague Gardens Cape Town +27(0) 21 534 1117 capesales@helukabel.co.za www.helukabel.co.za













